

# PRODUCT DATA SHEET

Long term corrosion protection by Denso

## DENSO BUTYL PRIMER H.W.

BUTYL TAPE PRIMER

### Description

DENSO BUTYL H.W. is a solvent based solution of synthetic rubbers and adhesion promoting resins.

### Uses

For application to cleaned metallic substrates prior to overwrapping with any of the range of DENSO butyl tapes.

### Features

- ❖ Promotes intimate contact between substrate and tape compound.
- ❖ Promotes high adhesion
- ❖ Fast drying
- ❖ Good wetting and penetration characteristics
- ❖ Can be applied by brush, roller or spray

### Application

Steel surfaces should be prepared to a minimum of St2. Apply a thin uniform coat of DENSO BUTYL PRIMER h.w. to cleaned substrate and allow to tack dry. Drying time will be dependent upon prevailing conditions.

Primed surfaces should be overcoated (taped) within approximately 8 hours of application, depending on site conditions, failing which re-priming is required.



/2.....  
(NC-P2)

The information on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed. In view of the constant research and development being undertaken in our laboratories we advise customers in their own interests to ensure that this data sheet has not been superseded by a more up to date publication. All products are sold subject to the Standard Condition of Sale, copies of which are available on request.

# DENSO BUTYL PRIMER H.W.

<b>Typical Properties</b>	Solids content	27 % m/m
	Viscosity @ 23° C F4cUp	35 secs.
	Flash point	-12° C
	Nominal coverage	6 m <sup>2</sup> /l
	Packaging	1l, 5l, 25l
<b>Safety</b>	Denso BUTYL Primer H.W. is flammable and should not be applied in the vicinity of naked flames or sources of ignition.	
	Avoid contact with the skin and the inhalation of vapours. Always ensure that adequate ventilation is provided	
<b>Storage</b>	Store in original containers in a cool, dry place away from sources of ignition	



FOR FURTHER INFORMATION PLEASE CONTACT YOUR NEAREST DENSO DEALER

Gauteng	Tel: 011 674-5412	Fax: 011 674-3956
Natal	031 569-4319	031 569-4328
Cape	021 557- 0257	021 556-1140
E.Cape	041 451-0818	041 451 0814
Namibia	09264 61 219606	09264 61 219616