

PRODUCT DATA SHEET

Long term corrosion protection by Denso

DENSO CLING WRAP

Description

Denso Cling Wrap is a heavy duty polyethylene copolymer film, which when wrapped upon itself under slight tension binds the individual layers tightly to themselves, thus needing no external securing.

Uses

Denso Cling Wrap is used as a protective outerwrap over Denso Mastic/Denso tape systems, particularly when applied to flanges , couplings and fittings.

Features

- ❖ Highly conformable
- ❖ Excellent impact resistance
- ❖ Excellent resistance to water and moisture vapour

Application

Denso Cling Wrap is wound spirally by hand with a 55% overlap. For optimum protection a third layer should be applied in a similar manner, giving a total of six layers of film thickness.



/2.....
(NC-C4)

The information on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed. In view of the constant research and development being undertaken in our laboratories we advise customers in their own interests to ensure that this data sheet has not been superseded by a more up to date publication. All products are sold subject to the Standard Condition of Sale, copies of which are available on request.

DENSO CLING WRAP

Typical Properties	Film thickness:	40 µm
	Colour	Transparent
	Roll length	250 m
	Roll width	100mm or 150mm
	(other roll widths can be supplied by arrangement)	
Safety	No special precautions required.	
Storage	Store in original packaging in a cool, dry place.	



FOR FURTHER INFORMATION PLEASE CONTACT YOUR NEAREST DENSO DEALER

Gauteng	Tel: 011 674-5412	Fax: 011 674-3956
Natal	031 569-4319	031 569-4328
Cape	021 557- 0257	021 556-1140
E.Cape	041 451-0818	041 451 0814
Namibia	09264 61 219606	09264 61 219616

NC-C4