PRODUCT DATA SHEET

Long term corrosion protection by Denso

P.S.A. 180 TAPE (WHITE & CLEAR)

Description

A modified polyethylene film coated with a pressure sensitive adhesive.

Uses

Used as an outerwrap over Denso petrolatum tapes for buried pipelines. Not recommended for exposed above ground applications. Clear tape can be used in many general applications as a reinforcing tape, for greenhouse repairs etc.

Features

- Highly conformable
- Impact and abrasion resistant for backfilling operations

Application

Spirally wrapped by hand or hand wrapping machines.





DENSO ULTRAFLEX P.S.A. 180 TAPE (WHITE & CLEAR)

Typical Properties

Film Thickness
Adhesive Thickness
Total Thickness
Tensile strength
Elongation at break
Roll length

Roll width Standard Colour

(Other colours available)

155 μm 25 μm 180 μm 15 Mpa min

>250% 33 m

48,96,150,200,250mm

White, clear

Safety No special precautions required.

Storage Store in original packaging in a cool, dry place.



FOR FURTHER INFORMATION PLEASE CONTACT YOUR NEAREST DENSO DEALER

 Gauteng
 Tel:
 011 674-5412
 Fax:
 011 674-3956

 Natal
 031 569-4319
 031 569-4328

 Cape
 021 557- 0257
 021 556-1140

 E.Cape
 041 451-0818
 041 451 0814

 Namibia
 09264 61 219606
 09264 61 219616

NC-P13