

PRODUCT DATA SHEET

Long term corrosion protection by Denso

DENSO S105 PASTE

Wet / Underwater Petrolatum Tape Primer

Description

A blend of saturated petroleum hydrocarbons, inert fillers and water displacing agents.

Uses

For the priming of metal surfaces prior to overwrapping with Denso Petrolatum Tapes. The presence of water displacing agents allows for the priming of 'cold' pipes or vessels where continuous moisture is present on the surface due to condensation.

Features

- ▶ Non-drying, non-hardening
- ▶ Can be applied to moist surfaces
- ▶ Good resistance to mineral acids, alkalis and salts

Application

Steel surfaces should be prepared to a minimum standard of St2. Apply a thin, even film of S105 Paste by means of a paint brush or clean rag.

Being a solvent free paste, there is no drying time required and Denso Tapes can be applied immediately after priming.

/2...
(S105 Paste)

The information on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products an information supplied by us for their own particular purposes. No patent liability can be assumed. In view of the constant research and development being undertaken in our laboratories, we advise customers in their own interests to ensure that this data sheet has not been superceded by a more up to date publication. All products are sold subject to the Standard Condition of Sale, copies of which are available on request.

DENSO S105 PASTE

Typical Properties	Specific gravity:	1.0
	Temperature range - Application:	5°C - 40°C
	Service:	60°C max
	Nominal coverage m ² /kg:	2 to 5
	Packaging:	5kg, 25kg

Safety: Avoid prolonged contact with the skin. Operators should wear oil-resistant gloves (PVC or Nitrile) or use a good proprietary barrier cream.

Storage: Store in original packaging in a cool, dry place.



LEADERS IN CORROSION PREVENTION
AND SEALING TECHNOLOGY

(S105 Paste)

FOR FURTHER INFORMATION PLEASE CONTACT YOUR NEAREST DENSO DEALER

Natal (H/O)	Tel: 031 569-4319	Fax: 031 569-4328
Gauteng	011 674-5412	011 674-3956
Cape	021 903-6063	021 903-6063
E. Cape	041 365-2711	041 365-2715
Namibia	09264 61 219606	09264 61 219616
E-Mail / Website:	bid@denso.co.za	www.denso.co.za