

PRODUCT DATA SHEET

Long term corrosion protection/sealing by Denso

DENSO 3000 SA

Self Adhesive Waterproofing Membrane

Product Description

A self adhesive waterproofing sheet, comprising an internal reinforcement of polyester carrier coated on both surfaces with a polymer modified bitumen adhesive compound. A light polythene top sheet is also present. The top sheet must be "torched-off" at the side & overlaps to provide a watertight bond and vapour barrier as well as providing protection to the concrete from attack by aggressive salts, such as chlorides and sulphates.

The concrete surface to which the membrane is to be applied must be dry, free of dust & any foreign particles and primed with a suitable Primer. The disposable release film must be removed from the self adhesive face just prior to laying the membrane to the primed surface.

The product has excellent "lay flat" properties. It is tough and durable and is particularly suitable for situations where there is a high risk of damage from site traffic during application.

Typical Data

Total Thickness:	3mm
Tensile Strength:	10 N/mm (min)
Puncture Strength:	345N
Elongation at Break:	300%
Adhesion Strength:	4 N/mm
Roll Weight:	32 kg
Roll Width:	950mm
Roll Length:	11m
Edge Laps:	100mm minimum
End Laps:	100mm minimum
Carton Size:	255 x 255 x 1100 mm

Advantages

- ▶ Factory controlled thickness
- ▶ Rapid sealing and bonding
- ▶ Fast and easy application
- ▶ Self sealing to minor damage
- ▶ High joint resistance to water pressure and water vapour transmission.

For further detailing on installation, please refer to our Application guide.

(Denso 3000SA MasterProofer) /2....

The information on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products an information supplied by us for their own particular purposes. No patent liability can be assumed. In view of the constant research and development being undertaken in our laboratories, we advise customers in their own interests to ensure that this data sheet has not been superceded by a more up to date publication. All products are sold subject to the Standard Condition of Sale, copies of which are available on request.

DENSO 3000 SA

Self Adhesive Waterproofing Membrane

Application

Full application instructions and Safety Data Sheets are available. This product must be laid in accordance with manufacturer's instructions.

Storage

Store in original packaging in a cool, dry place.
Recommended shelf life: 6 months

»»» § «««



LEADERS IN CORROSION PREVENTION
AND SEALING TECHNOLOGY

(Denso 3000SA-Master Proofer)

FOR FURTHER INFORMATION PLEASE CONTACT YOUR NEAREST DENSO DEALER

Natal (H/O)	Tel: 031 569-4319	Fax: 031 569-4328
Gauteng	011 674-5412	011 674-3956
Cape	021 903-6063	086261110405
E. Cape	041 365-5460	041 365-6475
Namibia	09264 61 219606	09264 61 219616
E-Mail / Website:	bid@denso.co.za	www.denso.co.za