

PRODUCT DATA SHEET

Long term corrosion protection/sealing by Denso

DENSO 4000 SA

Heavy Duty Self Adhesive Waterproofing Membrane

PRODUCT DESCRIPTION

A heavy duty self adhesive waterproofing sheet, comprising an internal reinforcement of polyester carrier coated on both surfaces with a polymer modified bitumen adhesive compound. A polythene top sheet is also present. The top sheet may be "torched" or scuffed by hand to provide a continuous bond at end laps. It is designed to provide a water and water vapour barrier, as well as providing protection to concrete from attack by aggressive salts, such as chlorides and sulphates.

The membrane is tough and durable and is particularly suitable for situations where there is a high risk of damage from site traffic during application.

TYPICAL DATA

Total Thickness:	4mm
Tensile Strength:	10 N/mm (min)
Puncture Strength:	345N
Elongation at Break:	300%
Adhesion Strength:	4 N/mm
Roll Weight:	32 kg
Roll Width:	950mm
Roll Length:	7,5m
Edge Laps:	100mm minimum
End Laps:	100mm minimum

ADVANTAGES

- ▶ Factory controlled thickness
- ▶ Rapid sealing and bonding
- ▶ Fast and easy application
- ▶ Self sealing to minor damage
- ▶ High joint resistance to water pressure and water vapour transmission.

For further detailing on installation, please refer to our Application Guide.



LEADERS IN CORROSION PREVENTION
AND SEALING TECHNOLOGY

(Denso 4000SA-Master Proofer)

FOR FURTHER INFORMATION PLEASE CONTACT YOUR NEAREST DENSO DEALER

Natal (H/O)	Tel: 031 569-4319	Fax: 031 569-4328
Gauteng	011 674-5412	011 674-3956
Cape	021 903-6063	021 906-2310
E. Cape	041 365-2711	041 365-2715
Namibia	09264 61 219606	09264 61 219616
E-Mail / Website:	bid@denso.co.za	www.denso.co.za